DATASHEET HYFIRE TAURUS MANUAL CALL POINT

TAU-CP-R-01

The TAU-CP-R-01 Hyfire Taurus Manual Call Point (MCP) is a fully intelligent device which is compatible with all Taurus translator and expander modules. The unit has a resettable plastic element, which displays a drop down warning indicator when operated. A key is supplied with the MCP for reset and case opening. The product is powered by two lithium CR123A batteries with a typical life of 10 years. A transparent cover protects against accidental operation, whilst a weatherproof enclosure is available for use outdoors or in hostile environments.






KEY FEATURES

- Bi-directional wireless communication
- Can be used with Taurus addressable and conventional translators
- 22 pairs of field channels
- Dual channel redundancy
- Long communication range (\cong 1 km in open air)
- 10 year battery life
- Utilises standard low-cost lithium battery technology
- Resettable element
- Easy scan & link programming option
- 3rd party approval to EN54-11 and EN54-25
- 5 years product warranty

TECHNICAL SPECIFICATION

Operating frequency range	868 – 870 MHz
Max radiated power	14dBm (25mW)
IP rating	42
Weight (without batteries)	160 g
Batteries	2x CR123A (3 V & 1.2 Ah)
Battery lifespan (typical)	10 years
Dimensions	88 x 87 x 61 mm
Operating Temperature	-10°C to +55°C
Max humidity (non condensing)	95% RH

TECHNICAL INFORMATION





Hyfire Wireless Fire Solutions Ltd, Unit B12a, Holly Farm Business Park Honiley, Warwickshire CV8 1NP

T: +44(0) 1926 485 282 E: info@hyfirewireless.co.uk hyfirewireless.com



- BS EN 54-11: Manual Call PointsBS EN 54-25: Components using
 - radio links and system requirements



CE

0051

DATASHEET HYFIRE TAURUS MANUAL CALL POINT



PROTECTIVE CALL POINT COVER

The Protective Call Point Cover dramatically reduces both misuse and the risk of accidental activation making it ideal for sports halls, manufacturingprocessing facilities, and other high-traffic areas. In addition, the Protective Call Point Cover ensures that two positive actions are required to activate the Call Point, making it suitable for territories where dualactivation is mandatory.



T: +44(0) 1926 485 282 E: info@hyfirewireless.co.uk hyfirewireless.com

