



CERTIFICATE OF CONSTANCY OF PERFORMANCE

0051 – CPR – 2177

In compliance with Regulation (EU) No. 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation, or CPR), this Certificate applies to the construction product

SOUNDER AND VISUAL ALARM DEVICE USING RADIO LINKS

Trademark: **HYFIRE**
Model: **TAU-MWSO-01 + HFC-WSR-03**

Other information: **see ANNEX**

Produced by:
STERLING SAFETY SYSTEMS LTD
Unit B12a, Holly Farm Business Park, Honiley Warwickshire CV8 1NP (UK)

In the manufacturing plant:
PI.Q0009R

This Certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 54-3:2001 + A1:2002 + A2:2006
EN 54-23:2010
EN 54-25:2008 + AC:2012

under system **1** are applied and that **the product fulfills all the prescribed requirements set out above.**

This certificate was first issued on 2020-11-03 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonized standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

ING. V. BAGGIO
CPR TECHNICAL DIRECTOR

Milan, 2020-11-03

This Certificate was issued by IMQ S.p.A., a Notified Body according to Regulation (EU) No. 305/2011.
IMQ S.p.A. Identification Number is: 0051.

ANNEX

0051 – CPR – 2177

Configuration

The sounder and visual alarm device model TAU-MWSO-01 + HFC-WSR-03 consists of a plastic enclosure (dimensions: 130 (d) x 90 (h) mm) with IP33C degree of protection, divided into:

- Wireless module model TAU-MWSO-01, containing:
 - No. 1 Main board (PCB code B40-ISWSM-0002);
 - No. 2 Battery allocable (CR123A Lithium, 3 V – 1.25Ah);
- Sounder and visual alarm device model HFC-WSR-03, containing:
 - No. 1 Main board (PCB code B20-CWS1X-1002);
 - No. 1 Piezoelectric buzzer;

Technical Characteristics

Tone patterns in compliance with EN 54-3:

- Warble Tone: 800 Hz for 500 ms then 1000 Hz for 500 ms;
- Continuous tone: 970 Hz continuous;
- Slow Whoop (Dutch): 500-1200 Hz for 3500 ms, then off for 500 ms;
- German DIN tone: 1200-500 Hz swept every 1000 ms (1 Hz);
- Coverage characteristics: W2.5-7;
- Flash rate: 0.5 Hz;
- Destination for use: Type B (for external);
- Operating frequency band: 868 MHz ; 916 MHz;
- Hardware identification of the microcontroller (U5 – PCB code B40-ISWSM-0002): STMicroelectronics, STM32L051R8;
- Firmware identification of the microcontroller (U5 – PCB code B40-ISWSM-0002): v. 1.0.2

List of optional functions with requirements (EN 54-23)

4.3.7 Synchronization